


ELECTRODE DEVICE FOR TRANSDUCING GENE AND DEVICE FOR TRANSDUCING GENE

Patent number: JP11290058 (A)
Publication date: 1999-10-26
Inventor(s): NAKAMURA HARUKAZU; MURAMATSU TATSUO +
Applicant(s): UNIQUE MEDICAL IMADA KK; TR TEC KK; TOKIWA SCIENCE KK; NAKAGAWA MASAHIDE +
Classification:
- international: *C12M1/00; C12N15/09; C12N5/00; C12N5/10; C12R1/91; C12M1/00; C12N15/09; C12N5/00; C12N5/10;* (IPC1-7): C12M1/00; C12N15/09; C12N5/10; C12N5/10; C12R1/91
- european:
Application number: JP19980115971 19980410
Priority number(s): JP19980115971 19980410

Abstract of JP 11290058 (A)

PROBLEM TO BE SOLVED: To provide an electrode device used for transducing a gene and capable of locally, safely and effectively transducing the gene, and to provide a device for transducing the gene. **SOLUTION:** The electrode device for transducing a gene is provided with a pair of electrodes 4, 5 and a holder for holding a pair of the electrodes so as to enable the alteration in the distance between a pair of electrodes. The respective electrodes have sheaths 8, 9 comprising an insulating material and conductors 10, 11 penetrating the sheaths, respectively. An inclined portion outward extended from the sheath and bent to the sheath and a contact 14 or 15 bent and continued to the inclined portion and used for bringing into contact with a target to be transduced are formed in each conductor 10 or 11. DC pulses are applied to the electrodes 4, 5 to generate electroporation.



Data supplied from the **espacenet** database — Worldwide